



Paradigm MilleniaSub™ MilleniaSub™

*Dual woofer back-to-back bipolar design! 900 Watts
Dynamic Peak Power / 300 Watts RMS Sustained
(Match with a MilleniaOne system)*



SPECIFICATIONS

Design	Dual driver, sealed box, vibration cancelling, built-in Ultra-Class-D™ power amplifier, built-in wireless receiver for wireless option, USB port for PBK equalization
Amplifier: High-Current, Discrete Output	900 watts Dynamic Peak / 300 watts RMS
Amplifier Features	Auto-on, soft clipping, thermal monitoring
Bass Drivers	Two 355-mm x 76-mm (14 in x 3 in) reinforced polymer cones, corrugated Santoprene® surrounds, 25-mm (1 in) voice-coils
Low-Frequency Extension*	21 Hz (DIN)
Subwoofer Cut-Off Frequency	Variable 35 Hz - 150 Hz; Bypass Option
Sub / Sat Phase Alignment	Variable 0° - 180°
Line-Level Input	RCA Sub-Out / LFE-Out of receiver, processor or other line-level source
Height, Width, Depth (Horizontal, Including Feet)	13.75 cm x 46.5 cm x 35.5 cm 5-1/2 in x 18-3/8 in x 14 in
Height, Width, Depth (Vertical, Including Stand)	38.25 cm x 12.5 cm (stand width 17.9 cm) x 46.5 cm (15 in x 4-7/8 in (stand width 7 in) x 18-3/8 in)
Height, Width, Depth (On-Wall, Including Hardware)	35.6 cm x 46.5 cm x 15.0 cm (14 in x 18-3/8 in x 5-7/8 in)
Weight (Unpacked)	10.9 kg / 24 lb each
Finishes	Satin Black, Satin White
Accessories (Sold Sep.)	Paradigm PT-2 Wireless Transmitter (see below) Paradigm Perfect Bass Kit room correction system MilleniaSub Wall-Mount Bracket system

* DIN 45 500. Indicates -3 dB in a typical listening room.



WIRELESS OPTION ONLY (USING PARADIGM PT-2 TRANSMITTER)

RF Frequency	2.4 GHz
Latency	Selectable (15 / 20 / 25 ms)

Transmission Range	50 ft / 15 m
Sampling Frequency / # Bits	48 kHz / 16 bits
Connectivity	Up to four subwoofers per PT-2 transmitter



PRODUCT IMAGES



Satin Black



Satin Black